



EXPERIENCE TO PERFORM

TECHNICAL DATA SHEET



SVITOL *PROFESSIONAL* FOOD LUBE



Nonfood Compounds
Program Listed

PRODUCT FEATURES

High purity white mineral oil spray lubricant with PTFE. Suitable for the lubrication and corrosion protection of all moving mechanisms in the food, cosmetic, pharmaceutical and packaging industries. Long-lasting lubricant, does not drip and has good adhesive power. PTFE improves the effectiveness and durability of lubrication. It contains antioxidants to maintain constant lubricating properties over time and EP additives for lubrication in harsh conditions. Recommended for applications between -30°C and +150°C. It does not contain silicone, colorless, odorless and tasteless. Can be used in case of accidental contact with food.

Applications

Product suitable for the lubrication of precision instruments, moving parts (textile machines, hinges, locks, pivot point). Particularly suitable for lubrication of sliding surfaces and food packaging equipment.

Ideal for protecting tools from corrosion. Clean and unlock moving parts

CLASSIFICATION

NSF H1 Nonfood Compounds Program Listed n.163342

AREA OF USE

Remove food and its packaging. Shake well before use and apply the amount necessary to ensure lubrication. If used to protect against corrosion, clean the piece well to remove any residue before use.

WARNINGS

Switch off before applying on electric equipment.

SHELF LIFE

In sealed packaging and stored at room temperature: at least 3 years.

PACKAGING

Cod. 4365 aerosol can 400 ml.

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user. For information, please contact our Technical Dept. on no. +39 02924361

AREXONS S.p.A. A SOCIO UNICO
Via Antica di Cassano, 23
20063 Cernusco sul Naviglio (MI) Italy
Capitale Sociale: € 15.000.000,00 I.V.
Registro delle Imprese di Milano n. 09728360968
Codice Fiscale e Partita IVA 09728360968
Direzione e coordinamento ex art. 2497 c.c. PLI (Netherlands) B.V.
Centralino 02 92436.1
Fax 02 92436.306
www.arexons.com

Sistemi di gestione di qualità della società Arexons S.p.A.
certificati ISO 9001 da LRQA.

Sistemi di gestione di ambiente e sicurezza della società Arexons S.p.A.
certificati ISO 14001 e OHSAS 18001 da Bureau Veritas.





EXPERIENCE TO PERFORM

TECHNICAL DATA SHEET

CHEMICAL & PHYSICAL PROPERTIES

• Apperance	Transparent
• Color	Uncoloured
• Density	0,85 g/ml
• Propellant	Bathane/ propane
• Flash point	-17°C
• Lubrificant oil properties	
Grade	NLGI 2
Working Penetration	265 – 295
Additives	PTFE / EP / AR
Range of temperature	-40°C +170°C

ADDITIONAL INFO

For information on product safety, please refer to the safety data sheet.

T.S. 28-03-2023

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user. For information, please contact our Technical Dept. on no. +39 02924361

AREXONS S.p.A. A SOCIO UNICO
Via Antica di Cassano, 23
20063 Cernusco sul Naviglio (MI) Italy
Capitale Sociale: € 15.000.000,00 I.V.
Registro delle Imprese di Milano n. 09728360968
Codice Fiscale e Partita IVA 09728360968
Direzione e coordinamento ex art. 2497 c.c. PLI (Netherlands) B.V.
Centralino 02 92436.1
Fax 02 92436.306
www.arexons.com

Sistemi di gestione di qualità della società Arexons S.p.A.
certificati ISO 9001 da LRQA.

Sistemi di gestione di ambiente e sicurezza della società Arexons S.p.A.
certificati ISO 14001 e OHSAS 18001 da Bureau Veritas.

